

OSHIMA


用途:

- 針對平織 / 針織裁片之黏合工作。
- 整匹布襯之黏合工作 (可搭配送 / 收料裝置)。

優點:

- 提高產能，連續黏接一貫作業，最高生產效率。
- 黏合寬度900mm/1000mm，長度無限。
- 自動皮帶修正裝置，確保上、下皮帶不偏離。
- 電子恒溫儀及固態繼電器控制恒溫系統，溫度偏差至最小極限。
- 加熱監控設備，控制發熱系統正常操作。
- 有6組電熱管，加熱系統傳熱均勻各種布料均可使用。

- 進口鐵氟龍黏合帶確保溫度均勻。
- 裝有防褶滾筒可處理各種布料。
- 配有網帶輸送系列，冷卻效果佳。
- 配有自動冷卻定溫停機裝置。
- 氣壓加壓裝置。
- 特殊設計之清潔布杆，徹底清潔皮帶，更換更容易。
- 選購：L皮帶加長。
- 選配：自動翻轉撥片，更容易撥離裁片。
- 出料方式採用可分離式的上下撥片裝置，讓布料於出口自然的被剝離皮帶，不會產生皺折。



OP-900

Application:

- For the woven/knitted fabrics fusing.
- Fusing for the whole roll of fabric and interline. Machine can work together with feeding conveyor and collecting stacker as option.

Feature:

- Continuous fusing system increases the productivity.
- The fusing width is 900mm and the length is endless.
- PCB and micro switch control the upper & lower belts automatically.
- Electronic thermostat and the relay controller to offer the stable temperature and minimum the temperature differences to the minimum.
- The heating areas are well monitored, to ensure the heating system working normally.
- There are 6 heaters to distribute the heat evenly and can be used to all fabrics.

- The best quality of Teflon belt assures the precise temperature.
- With the wrinkle-free silicone roller to handle with all fabrics in perfect bonding.
- With the cooling fan and mesh conveyor belt, which has the best cooling effect.
- Auto cooling Function is automatically started once machine is switched to power off.
- Standard Air-pressure system.
- Special-designed clean rod to clean the belt completely, and it is easy for replacement once the rod gets dirty.
- Optional: L: Longer bottom belt.
- Rotary Strip-off device for strengthening the stripping function and avoid transforming on the finished fabrics.

規格 Specification

型號Model	OP-900A	OP-900LA	OP-1000A	OP-1000LA
電壓Power Supply	3P 220V/380V			
馬達功率Motor	240W			
電熱功率Heater	12 KW	12.6 KW	14.4 KW	15 KW
使用氣壓Use Air Pressure	0.2~0.5 Mpa			
設定溫度Temperature	常溫~200°C			
黏合寬度Fusing Width	900 mm		1000 mm	
黏合時間Fusing Time	5~30 Sec			
選配空壓Supply Air Pressure	最小消耗量Min. Consumption 5~10L/H			
機器尺寸L×W×H Dimensions	3310x1660x1420mm	3310x1660x1420mm	3310x1760x1420mm	3310x1760x1420mm
裝箱尺寸L×W×H Packing Volume	2300x1640x1500mm	2480x1640x1500mm	2300x1730x1510mm	2500x1730x1520mm
淨重/毛重N.W / G.W	660/720 kg		790/860 kg	

*產品規格和內容,如有更改,恕不另行通知 *Design and specifications subject to change without prior notice

2019.01.04

台灣歐西瑪股份有限公司 Tel: 886-2-2268-3311
OSHIMA CO.,LTD. Fax: 886-2-2269-5000
 http: www.oshima.com.tw / E-mail: info@oshima.com.tw

上海歐西瑪服裝設備有限公司
OSHIMA (SHANGHAI) CO.,LTD.
 Tel: 86-21-5486-8787 / Tel: 86-573-8858-5538

連續式黏合機 OP-900A/LA/1000A/LA
 CONTINUOUS FUSING PRESS MACHINE